







LiFeBATT Battery Chargers

Features:

1. 3 Stages charging: 1st-25% of rating current; 2nd-50% of rating current; 3rd-100% of rating current (equalizer).
2. Automatic Re-charging Battery: If the battery voltage $< @3.1V/cell$ after full charged, the charger will automatic re-charging the battery.
3. Short-circuit Protection: Charger O/P cut-off automatically when short circuit
4. Overload Protection: Charger O/P current-limited automatically when overload.
5. Reverse Polarity Protection: Charger O/P cut-off automatically when battery reverses connection.
6. Unique Digital Meter Display: Indicating charging voltage, current, battery capacity (percent and AH) and charger timer.
7. 3 LED Display: Red (power), green (full charged) & orange (equalizer charge)

	Spec. Model	Description	Specifications	Price FOB Danville, VA		
1	LBC-08230D		323x231x106 mm / 4.2Kgs I/P: 100~120Vac O/P: 29.2Vdc/23A (24V/23A)	\$ 276.00		
				With 1.2Meter O/P wires		
2	LBC-08450D		480x355x87.5 mm / 8.5Kgs I/P: 100~120Vac O/P: 29.2Vdc/45A (24V/45A)	\$ 465.00		
				With 1.2Meter O/P wires		
3	LBC-12150D		323x231x106 mm / 4.2Kgs I/P: 100~120Vac O/P: 43.8Vdc/15A (36V/16A)	\$ 286.00		
				With 1.2Meter O/P wires		
4	LBC-12300D		480x355x87.5 mm / 8.5Kgs I/P: 100~120Vac O/P: 43.8Vdc/30A (36V/30A)	\$ 499.00		
				With 1.2Meter O/P wires		
5	LBC-16220D		480x355x87.5 mm / 8.5Kgs I/P: 100~120Vac O/P: 58.4Vdc/22A (48V/22A)	\$ 499.00		
				With 1.2Meter O/P wires		
6	LBC-24150D		480x355x87.5 mm / 8.5Kgs I/P: 100~120Vac O/P: 87.6Vdc/15A (72V/15A)	\$ 550.00		
				With 1.2Meter O/P wires		